ø30 TWN/TWND Series

Accessories

lot		,						
ilot Lights	Shape		Material	al Part No.		Ordering No.	Package Quantity	Remarks
	Button Cover for Extended Pushbuttons		Nitril rubber Re	Black	0C-11B	0C-11B	1	 Metallic bezels covered with a rubber boot to enhance waterproof characteristics. Button is not included. Applicable to extended pushbuttons only. Oil-proof Operating temperature: -5 to +60°C.
APEM Switches &				Red	0C-11R	0C-11R		
Pilot Lights								
Control Boxes Emergency				Green	0C-11G	0C-11G		
Stop Switches Enabling Switches	For T	WN/TWND		Yellow	0C-11Y	0C-11Y		<u>/ M30 P1.5</u>
Safety Products	For flush pushbuttons For extended pushbuttons		EPDM rubber	0C-121 0C-122			1	Used to cover and protect push- buttons where units are subject to water splash. Not suitable for outdoor use or where the units are subject to oil splash.
Explosion Proof						0C-121		
Terminal Blocks						0C-122 1		
Relays & Sockets Circuit Protectors							1	Part No. A B 0C-121 37 16 0C-122 37 22
Power Supplies	For TWN/TWND Dust-proof Rubber Cover							Used for ABN4G and ABGD4 Panel Thickness
LED Illumination	for Jumbo Mushrooms			OC-4GN		OC-4GN	1	pushbuttons.
Controllers			Nitril rubber (black)					
Operator Interfaces								
Sensors	For TWN/TWND Padlock Cover							Used to protect pushbuttons and illuminated pushbuttons
AUTO-ID	For TWN/TWND Padlock Cover for Key Selector Switches			OL-KL1		OL-KL1	1	 (momentary/maintained) with 24 mm max. height from the panel, and selector switches (knob operator). Not used for the following models. Pushbuttons
Flush Silhouette ø16			Polyarylate (gasket: nitryl rubber)					Mushroom with full shroud 82.5 Mushroom 0.8 to 3.2 Jumbo mushroom with shroud 3.2
ø22 ø30								Illuminated Outside diameter: s50 Pushbuttons Inside diameter: s44 With half shroud Image: shroud shr
Miniature Pilot Lights								With full shroud <u>Selector Switches</u> Lever operator Key selector switch with <u>Key Hole 08</u> <u>Key Hole 08</u>
								Key selector switch with key installed
TWN TWND ARN CS			Metal Paint: red (zinc-plated brass)	HS9Z-PC30		HS9Z-PC30	1	• Applicable model <u>Key selector switches ASN K/ASD K</u> See padlock cover catalog for operating instruction. ^{15 mm-thick} <u>Metrid: SRed</u> <u>Americ: Stred</u> <u>2 mm-thick</u> <u>4 dot</u> <u>4 dot</u> <u></u>
l	For Flush Pushbuttons							 Used to protect flush pushbuttons from inadvertent operation. Can be easily attached using the locking ring.
	For T	WN/TWND	Metal (zinc-plated brass)	OL-C		OL-C	1	seture 2 billion of the seture