










Maintenance Parts			All dimensions in mm.			
Shape	Material	Part No.	Ordering No.	Package Quantity	Color Code * / Remarks	
Selector Operator 	Polyacetal	① Knob ø22.4, height 19	ASSHHY-*	ASSHHY- *PN02	2	B (black), G (green), R (red)
		③ Color Insert Width 19, depth 5, height 18.5	TWS-HC1*	TWS-HC1 *PN05	5	B (black), G (green), R (red), S (blue), Y (yellow), W (white)
	AS resin	④ Illuminated Selector ø20.4, height 20.2	ASLSLDY-*	ASLSLDY-*	1	G (green), R (red), S (blue)
			ASLSDDY-*	ASLSDDY-*		A (amber), W (white), Y (yellow)
Cap for Key Selector ø20.4, height 14 	Polyacetal	AKS2B-*	AKS2B- *PN05	5	B (black), R (red)	
Clears Button Cover 	Polycarbonate	ABS1B-C	ABS1B- CPN05	5	B (black), G (green), R (red), W (white), Y (yellow) Used on flush pushbuttons to indicate a mark or a symbol engraved on the marking plate. The clear button cover holds the marking plate.	
	Polyacetal	TWS-0*	TWS-0 *PN10	10		
Marking Plate 	Acrylic	① For Square Pilot Lights and Illuminated Pushbuttons □21.2, thickness 1	UPQS106P-*	UPQS106P- *PN02	2	W (white), C (clear) Engraving area: □19.2, 0.5 mm thick max.
		② For Square Pilot Lights with Metal Bezel □20, thickness 2	UPQS306N-W	UPQS306N- WPN02		W (white) only Engraving area: □19.2, 0.5 mm thick max.
Contact Block HW-U  Weight: 11 g (approx.)	1NO	HW-U10	HW-U10	1	Housing: Blue Push rod: Green -MAU: gold contact	
		HW-U10-MAU	HW-U10-MAU			
	1NC	HW-U01	HW-U01	1	Housing: Purple red Push rod: Red -MAU: gold contact	
		HW-U01-MAU	HW-U01-MAU			
	EM contact (early make)	HW-U10R	HW-U10R	1	Housing: Blue Push rod: Black -MAU: gold contact	
		HW-U10R-MAU	HW-U10R-MAU			
LB contact (late break)	HW-U01R	HW-U01R	1	Housing: Purple red Push rod: White -MAU: gold contact		
	HW-U01R-MAU	HW-U01R-MAU				
Dummy Block  Weight: 3.5 g (approx.)	Polyamide	HW-DB	HW-DB PN10	10	For HW-U contact blocks Used when total number of contact blocks and full voltage adapters is odd.	
Full Voltage Adapter For illuminated unit (*1)  Weight: 12 g (approx.)	Polyamide	HW-GA1N	HW-GA1 NPN02	2	Applicable model: Illuminated pushbuttons Illuminated selector switches Applicable load (LED lamp) LSTD-6 (6V AC/DC) LSTD-1 (12V AC/DC) LSTD-2 (24V AC/DC)	
Transformer (*1)  Weight: 65 g (approx.)	100/110V AC	HW-T16	HW-T16	1	Applicable model: Pilot lights Illuminated pushbuttons Illuminated selector switches Applicable load (LED lamp) LSTD-6 (6V AC/DC)	
	200/220V AC	HW-T26	HW-T26			
Contact Block Plug 	Polyamide	HW9Z-CBPL	HW9Z-CBPL PN10	10	Used to plug the hole in the center of contact block.	

*1) For use as maintenance parts. Do not use for expansion or remodelling purposes.