

Servo applications • PVC sheath



# ÖLFLEX® SERVO 2YSLCY-JB

EMC-optimised motor cable, low-capacitance, double screened



**Info**

- EMC-optimised design
- 4-core design in transparent or black
- 3+3 symmetry reduces common-mode interference effects

**Technical data**

**Classification**  
 ETIM 5.0 Class-ID: EC000057  
 ETIM 5.0 Class-Description: Low voltage power cable

**Core identification code**  
 Colours according to HD 308 S2  
 VDE 0293-308

**Conductor stranding**  
 Fine wire according to VDE 0295  
 Class 5 / IEC 60228 Class 5

**Minimum bending radius**  
 Occasional flexing: 15 x outer diameter  
 Fixed installation: 4 x outer diameter

**Nominal voltage**  
 U<sub>0</sub>/U: 600/1000 V

**Test voltage**  
 Core/Core: 4 kV  
 Core/Screen: 4 kV

**Protective conductor**  
 G = with GN-YE protective conductor  
 X = without protective conductor  
 Protective conductor of 3+3 version is gusset-filling divided between power cores

**Temperature range**  
 Flexing: -5°C to +70°C  
 3+3 core version: -15°C to +70°C  
 Fixed installation: -40°C to +70°C

**Benefits**

- EMC-compliant installation of power drive systems conforming to EN 61800-3
- High power transmission for large drives
- Longer cable connection possible between frequency converter and drive due to low capacitance design
- Symmetrical 3+3 Version supports the reduction of bearing currents
- Versions with black outer sheath are suitable for outdoor use and direct burial

**Application range**

- Connecting cable between frequency converter and motor
- In dry, damp or wet interiors
- Paper industry
- Chemical industry
- Heavy industry

**Product features**

- Flame-retardant according IEC 60332-1-2

**Norm references / Approvals**

- Based on VDE 0207 / 0250 / 0295

**Product Make-up**

- Fine-wire, bare copper conductor
- Core insulation: PE
- Cores twisted concentrically (symmetrically splitted protective conductor of 3+3 version is gusset-filling divided between the power cores)
- Screening: wrapping of laminated aluminium foil in combination with tinned copper braiding
- 4-core version: optional transparent or black PVC outer sheath
- 3+3 core version: PVC outer sheath, black - cold flexible

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
<b>ÖLFLEX® SERVO 2YSLCY-JB / 4-core version - transparent outer sheath</b>				
0036425	4 G 1.5	11.4	95	230
0036426	4 G 2.5	12.4	150	300
0036427	4 G 4	15.6	235	485
0036428	4 G 6	17.0	320	630
0036429	4 G 10	19.6	533	860
0036430	4 G 16	22.1	789	1290
0036431	4 G 25	26.3	1236	1860
0036432	4 G 35	29.5	1662	2610
0036433	4 G 50	35.8	2345	2950
0036434	4 G 70	40.3	3196	3950
0036435	4 G 95	46.5	4316	5300
0036436	4 G 120	53.2	5435	6600
0036437	4 G 150	57.3	6394	7043
0036438	4 G 185	62.3	7639	8384
<b>ÖLFLEX® SERVO 2YSLCY-JB BK / 4-core version - black outer sheath</b>				
1136450	4 G 1.5	11.4	95	230
1136451	4 G 2.5	12.4	150	300
1136452	4 G 4	15.6	235	485
1136453	4 G 6	17.0	320	630
1136454	4 G 10	19.6	533	860
1136455	4 G 16	22.1	789	1290
1136456	4 G 25	26.3	1236	1860

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
1136457	4 G 35	29.5	1662	2610
1136458	4 G 50	35.8	2345	2950
1136459	4 G 70	40.3	3196	3950
1136460	4 G 95	46.5	4316	5300
1136461	4 G 120	53.2	5435	6600
1136462	4 G 150	57.3	6394	7043
1136463	4 G 185	62.3	7639	8384
<b>ÖLFLEX® SERVO 2YSLCYK-JB / 3+3 core version - black outer sheath, cold flexible</b>				
0036439	3 X 1,5 + 3 G 0,25	11.4	88	140
0036440	3 X 2,5 + 3 G 0,5	12.2	144	220
0036441	3 X 4 + 3 G 0,75	14.4	224	323
0036442	3 X 6 + 3 G 1,0	15.7	276	420
0036443	3 X 10 + 3 G 1,5	18.0	491	615
0036444	3 X 16 + 3 G 2,5	20.2	723	819
0036445	3 X 25 + 3 G 4	23.8	1136	1325
0036446	3 X 35 + 3 G 6	26.9	1535	1718
0036447	3 X 50 + 3 G 10	32.6	2156	2399
0036448	3 X 70 + 3 G 10	36.4	2871	3056
0036449	3 X 95 + 3 G 16	42.0	3953	4162
0036450	3 X 120 + 3 G 16	47.8	4836	5074
0036451	3 X 150 + 3 G 25	51.6	5412	6128
0036479	3 X 185 + 3 G 35	56.5	7041	7500
0036453	3 X 240 + 3 G 50	65.1	8986	9770

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.  
 Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.  
 Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)  
 Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum  
 Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).  
 Photographs are not to scale and do not represent detailed images of the respective products.

**Similar products**

- ÖLFLEX® SERVO 9YSLCY-JB refer to page 104

**Accessories**

- SKINTOP® BRUSH ADD-ON refer to page 734
- SKINTOP® MS-SC-M refer to page 732
- SKINTOP® MS-M BRUSH refer to page 733