

固定用(円筒面)のみぞ寸法及び形状(JIS-B-2401、JIS-B-2406)

G 円筒

呼 び 番 号	O リング実寸法				みぞ部の寸法														
					軸 径		参 考			穴 径									
	d ₂		d ₁		d		dの許容差に相当するハメアイ記号			D									
*G 3	3.1	± 0.10	2.4	± 0.14															
*G 4			3.4	± 0.14															
*G 5			4.4	± 0.15															
*G 6			5.4	± 0.15															
*G 7			6.4	± 0.16															
*G 8			7.4	± 0.16															
*G 9			8.4	± 0.17															
*G 10			9.4	± 0.17															
*G 11			10.4	± 0.18															
*G 12			11.4	± 0.18															
*G 13			12.4	± 0.19															
*G 14			13.4	± 0.19															
*G 15			14.4	± 0.20															
*G 16			15.4	± 0.20															
*G 17			16.4	± 0.21															
*G 18			17.4	± 0.21															
*G 19			18.4	± 0.22															
*G 20			19.4	± 0.22															
*G 21			20.4	± 0.23															
*G 22			21.4	± 0.24															
*G 23			22.4	± 0.24															
*G 24			23.4	± 0.24															
G 25			3.1	± 0.10								24.4	± 0.25	25	h9	f8	e9	30	+0.10 0
G 30												29.4	± 0.29	30				35	
G 35	34.4	± 0.33			35	40													
G 40	39.4	± 0.37			40	45													
G 45	44.4	± 0.41			45	50													
G 50	49.4	± 0.45			50	55													
*G 52	51.4	± 0.47			52	57													
G 55	54.4	± 0.49			55	60													
*G 58	57.4	± 0.51			58	63													
G 60	59.4	± 0.53			60	65													
*G 62	61.4	± 0.54			62	67													
*G 63	62.4	± 0.55			63	68													
*G 64	63.4	± 0.56			64	69													
G 65	64.4	± 0.57			65	70													
*G 67	66.4	± 0.59			67	72													
G 70	69.4	± 0.61			70	75													
*G 72	71.4	± 0.63			72	77													
G 75	74.4	± 0.65			75	80													
G 80	79.4	± 0.69			80	85													
G 85	84.4	± 0.73			85	90													
G 90	89.4	± 0.77			90	95													
G 95	94.4	± 0.81			95	100													
G 100	99.4	± 0.85			100	105													
G 105	104.4	± 0.87			105	110													
G 110	109.4	± 0.91			110	115													
G 115	114.4	± 0.94			115	120													
G 120	119.4	± 0.98			120	125													
G 125	124.4	± 1.01			125	130													
G 130	129.4	± 1.05			130	135													
G 135	134.4	± 1.08			135	140													
G 140	139.4	± 1.12			140	145													
G 145	144.4	± 1.16	145	150															

*印は JIS 規格外寸法です。