

## 固定用 (円筒面) のみぞ寸法及び形状

呼び番号	Oリング寸法 (mm)		みぞ部の寸法					
	太さ $d_2$	内径 $d_1$	d	D	みぞ幅 $G_0^{+0.25}$			E 最大
					バックアップ リングなし	バックアップ リング 1個	バックアップ リング 2個	
GS 150	3.1 ± 0.1	149.3 ± 1.19	150	155	4.1	5.6	7.3	0.08
GS 155		154.3 ± 1.23	155	160				
GS 160		159.3 ± 1.26	160	165				
GS 165		164.3 ± 1.30	165	170				
GS 170		169.3 ± 1.33	170	175				
GS 175		174.3 ± 1.37	175	180				
GS 180		179.3 ± 1.40	180	185				
GS 185		184.3 ± 1.44	185	190				
GS 190		189.3 ± 1.47	190	195				
GS 195		194.3 ± 1.51	195	200				
GS 200		199.3 ± 1.55	200	205				
GS 205		204.3 ± 1.58	205	210				
GS 210		209.3 ± 1.61	210	215				
GS 215		214.3 ± 1.65	215	220				
GS 220		219.3 ± 1.68	220	225				
GS 225		224.3 ± 1.71	225	230				
GS 230		229.3 ± 1.75	230	235				
GS 235		234.3 ± 1.78	235	240				
GS 240		239.3 ± 1.81	240	245				
GS 245		244.3 ± 1.85	245	250				
GS 250		249.3 ± 1.88	250	255				
GS 255		254.3 ± 1.91	255	260				
GS 260		259.3 ± 1.94	260	265				
GS 265		264.3 ± 1.98	265	270				
GS 270		269.3 ± 2.01	270	275				
GS 275		274.3 ± 2.04	275	280				
GS 280		279.3 ± 2.07	280	285				
GS 285		284.3 ± 2.11	285	290				
GS 290		289.3 ± 2.14	290	295				
GS 295		294.3 ± 2.17	295	300				
GS 300	299.3 ± 2.20	300	305					
GS 305	304.3 ± 2.24	305	310					
GS 310	309.3 ± 2.27	310	315					
GS 315	314.3 ± 2.30	315	320					
GS 320	319.3 ± 2.33	320	325					
GS 325	324.3 ± 2.36	325	330					
GS 330	329.3 ± 2.39	330	335					
GS 335	334.3 ± 2.42	335	340					
GS 340	339.3 ± 2.45	340	345					
GS 345	344.3 ± 2.48	345	350					
GS 350	349.3 ± 2.51	350	355					
GS 355	354.3 ± 2.54	355	360					
GS 360	359.3 ± 2.57	360	365					
GS 365	364.3 ± 2.60	365	370					
GS 370	369.3 ± 2.63	370	375					
GS 375	374.3 ± 2.67	375	380					
GS 380	379.3 ± 2.70	380	385					
GS 385	384.3 ± 2.73	385	390					
GS 390	389.3 ± 2.77	390	395					
GS 395	394.3 ± 2.79	395	400					
GS 400	399.3 ± 2.82	400	405					
GS 405	404.3 ± 3.00	405	410					
GS 410	409.3 ± 3.00	410	415					
GS 415	414.3 ± 3.00	415	420					
GS 420	419.3 ± 3.00	420	425					
GS 425	424.3 ± 3.00	425	430					
GS 430	429.3 ± 3.00	430	435					
GS 435	434.3 ± 3.00	435	440					
GS 440	439.3 ± 3.00	440	445					
GS 445	444.3 ± 3.00	445	450					
GS 450	449.3 ± 3.00	450	455					