




SCX-N Hex Nuts - Ceramic

Selection Tool
 CAD Download
 Heat-resistance
 Chemical-proof



- Ceramic made from 99.5% high-purity alumina.
- Usable continually at 1500 deg C.
- They have excellent heat resistance, chemical resistance, and electrical insulation.
- The properties of ceramic screws → P.653

● Application

FPD production equipment, semiconductor devices, printed circuit board etching devices, metallic surface treatment equipment and facilities, and chemical plants

● Material/Finish

RoHS Compliant

	SCX-N
Main Body	Al ₂ O ₃ (99.5% Alumina)

SCX-N Hex Nuts

Unit : mm

Part Number	M	B	T	Mass (g)	Qty per pack
SCX-M3-N	M3	5.5	2.3	0.16	1
SCX-M4-N	M4	7	3.1	0.38	1
SCX-M5-N	M5	8	4.6	0.68	1
SCX-M6-N	M6	10	5	1.2	1
SCX-M8-N	M8	13	6.7	2.8	1
SCX-M10-N	M10	16	8.2	5.1	1

- Part number specification

SCX-M5-N



Individual Sales → P.794	Cleanroom Wash & Packaging → P.792	Screw Length Adjustment → P.796	Vibration Resistant → P.795	Modification process for captive use → P.791
1 pc. in 1 bag	Available / Add'l charge	Not Available	Not Available	Not Available