


●耐凝着性に優れたコーティングでアルミおよび銅加工に最適です。

This drill specially coated is most suitable for Aluminum and Copper.



オーダ方法

RGASD 直径

単位 (Unit) : mm

直径 Dc	溝長 ℓ	全長 L	在庫 Stock
1.0	12	34	
1.01			
1.02			
1.03			
1.04			
1.05			
1.06			
1.07			
1.08			
1.09			
1.1	14	36	
1.11			
1.12			
1.13			
1.14			
1.15			
1.16			
1.17			
1.18			
1.19			
1.2	16	38	
1.21			
1.22			
1.23			
1.24			
1.25			
1.26			
1.27			
1.28			
1.29			
1.3	18	40	
1.31			
1.32			
1.33			
1.34			
1.35			
1.36			
1.37			
1.38			
1.39			
1.4	20	43	
1.41			
1.42			
1.43			
1.44			
1.45			
1.46			
1.47			
1.48			
1.49			
1.5	27	53	
1.51			
1.52			
1.53			
1.54			
1.55			
1.56			
1.57			
1.58			
1.59			
1.6	30	57	
1.61			
1.62			
1.63			
1.64			
1.65			
1.66			
1.67			
1.68			
1.69			
1.7	36	65	
1.71			

直径 Dc	溝長 ℓ	全長 L	在庫 Stock
1.72	20	43	
1.73			
1.74			
1.75			
1.76			
1.77			
1.78			
1.79			
1.8			
1.81			
1.82	22	46	
1.83			
1.84			
1.85			
1.86			
1.87			
1.88			
1.89			
1.9			
1.91			
1.92	24	49	
1.93			
1.94			
1.95			
1.96			
1.97			
1.98			
1.99			
2.0			
2.01			
2.02	27	53	
2.03			
2.04			
2.05			
2.06			
2.07			
2.08			
2.09			
2.1			
2.11			
2.12	30	57	
2.13			
2.14			
2.15			
2.16			
2.17			
2.18			
2.19			
2.2			
2.21			
2.22	33	61	
2.23			
2.24			
2.25			
2.26			
2.27			
2.28			
2.29			
2.3			
2.31			
2.32	36	65	
2.33			
2.34			
2.35			
2.36			
2.37			
2.38			
2.39			
2.4			
2.41			
2.42	39	70	
2.43			

直径 Dc	溝長 ℓ	全長 L	在庫 Stock
2.44	30	57	
2.45			
2.46			
2.47			
2.48			
2.49			
2.5			
2.51			
2.52			
2.53			
2.54	33	61	
2.55			
2.56			
2.57			
2.58			
2.59			
2.6			
2.61			
2.62			
2.63			
2.64	36	65	
2.65			
2.66			
2.67			
2.68			
2.69			
2.7			
2.71			
2.72			
2.73			
2.74	39	70	
2.75			
2.76			
2.77			
2.78			
2.79			
2.8			
2.81			
2.82			
2.83			
2.84	43	75	
2.85			
2.86			
2.87			
2.88			
2.89			
2.9			
2.91			
2.92			
2.93			
2.94	46	80	
2.95			
2.96			
2.97			
2.98			
2.99			
3.0			
3.01			
3.02			
3.03			
3.04	49	85	
3.05			
3.06			
3.07			
3.08			
3.09			
3.1			
3.11			
3.12			
3.13			
3.14	52	90	
3.15			

直径 Dc	溝長 ℓ	全長 L	在庫 Stock
3.16	36	65	
3.17			
3.18			
3.19			
3.2			
3.21			
3.22			
3.23			
3.24			
3.25			
3.26	39	70	
3.27			
3.28			
3.29			
3.3			
3.31			
3.32			
3.33			
3.34			
3.35			
3.36	42	75	
3.37			
3.38			
3.39			
3.4			
3.41			
3.42			
3.43			
3.44			
3.45			
3.46	45	80	
3.47			
3.48			
3.49			
3.5			
3.51			
3.52			
3.53			
3.54			
3.55			
3.56	48	85	
3.57			
3.58			
3.59			
3.6			
3.61			
3.62			
3.63			
3.64			
3.65			
3.66	51	90	
3.67			
3.68			
3.69			
3.7			
3.71			
3.72			
3.73			
3.74			
3.75			
3.76	54	95	
3.77			
3.78			
3.79			
3.8			
3.81			
3.82			
3.83			
3.84			
3.85			
3.86	57	100	
3.87			

総目次

CrN

穴深さ

~3D

~5D

~8D

深穴

フラット・座ぐり

センタリング

ノスドリル

鉄骨

油穴付き

アルミ・非鉄金属

ストレート

テーパ