



番号	内輪を使用する場合				内輪なしの質量(g)		
	総ころ形 開放形	内輪呼び番号	主要寸法(mm) 取付関係寸法(mm)			(参考) 開放形	
			d	B	$d_a$ (最小)	$r_a$ (最大)	
—	—	—	—	—	—	—	1.3
—	—	—	—	—	—	—	1.7
—	—	—	—	—	—	—	2.2
—	—	—	—	—	—	—	2.3
—	—	—	—	—	—	—	2.7
FH-810	MFH-810	—	—	—	—	—	3.2
—	—	—	—	—	—	—	5.2
—	—	—	—	—	—	—	6.0
FH-910	MFH-910	—	—	—	—	—	3.6
—	—	—	—	—	—	—	5.7
—	—	—	—	—	—	—	6.4
FH-1010	MFH-1010	FIR-71010 FIR-71010 FIR-71010	7 7 7	10.5 10.5 10.5	9 9 9	0.3 0.3 0.3	3.6 6.1 6.9
—	—	FIR-81210 FIR-81212 FIR-81212	8 8 8	10.5 12.5 12.5	10 10 10	0.3 0.3 0.3	4.1 7.7 10
FH-1212	MFH-1212	—	—	—	—	—	4.5 8.2 11
F-1312	MF-1312	FIR-101312 FIR-101312	10 10	12.5 12.5	12 12	0.3 0.3	8.6 11
F-1412	MF-1412	FIR-101412 FIR-101412	10 10	12.5 12.5	12 12	0.3 0.3	10 12
F-1416	MF-1416	FIR-101416 FIR-101416	10 10	16.5 16.5	12 12	0.3 0.3	13 18
F-1512	MF-1512	FIR-121512	12	12.5	14	0.3	10
F-1514	MF-1514	FIR-121512	12	12.5	14	0.3	12
—	—	—	—	—	—	—	11 14 16
F-1516	MF-1516	FIR-121516 FIR-121516	12 12	16.5 16.5	14 14	0.3 0.3	13 17
—	—	—	—	—	—	—	14 18
F-1612	MF-1612	FIR-121612 FIR-121612	12 12	12.5 12.5	14 14	0.3 0.3	11 14
F-1616	MF-1616	FIR-121616 FIR-121616	12 12	16.5 16.5	14 14	0.3 0.3	12 15
—	—	—	—	—	—	—	15 18 20