


35° DIAMOND TYPE POSITIVE INSERT

Indexable Inserts for Turning

Indexable Inserts

VP 35° Diamond Type
11° Relief
With Insert Hole



Information in "Shape" column

(Legend) Continuous Cut ● : 1st Choice ○ : 2nd Choice Medium Cut ● : 1st Choice ○ : 2nd Choice Interrupted Cut ★ : 1st Choice ☆ : 2nd Choice

B
Positive Inserts

VP 0802

- l : 8.3
- s : 2.38
- ϕd : 4.76
- ϕd_1 : 2.4

Recommended Application	Coat													Coated Cermet	Cermet		Carbide																
	AC810P	AC820P	AC830P	AC2000	AC610M	AC630M	AC6030M	AC6040M	AC405K	AC415K	AC420K	AC410K	AC503U	AC510U	AC520U	AC530U	ACZ150	T1500Z	T3000Z	T2000Z	T1000A	T1500A	T110A	T1200A	ST10P	ST20E	A30	G10E	EH510	EH520	H1		
P steel	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
M stainless steel	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
K cast iron	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
N non-ferrous metal	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
S exotic alloy	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
H hardened steel	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

C

D

R

S

Shape	Cat. No.	r_E
FX Finishing 15°	VPET 0802008R-FX	0.08
	0802008L-FX	0.08
	0802015R-FX	0.15
	0802015L-FX	0.15
	0802018R-FX	0.18
	0802018L-FX	0.18
FY Finishing 15°	VPET 0802008R-FY	0.08
	0802008L-FY	0.08
	0802015R-FY	0.15
	0802015L-FY	0.15
	0802018R-FY	0.18
	0802018L-FY	0.18

T

V

VP 1103

- l : 11.1
- s : 3.18
- ϕd : 6.35
- ϕd_1 : 2.8

Recommended Application	Coat													Coated Cermet	Cermet		Carbide																
	AC810P	AC820P	AC830P	AC2000	AC610M	AC630M	AC6030M	AC6040M	AC405K	AC415K	AC420K	AC410K	AC503U	AC510U	AC520U	AC530U	ACZ150	T1500Z	T3000Z	T2000Z	T1000A	T1500A	T110A	T1200A	ST10P	ST20E	A30	G10E	EH510	EH520	H1		
P steel	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
M stainless steel	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
K cast iron	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
N non-ferrous metal	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
S exotic alloy	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
H hardened steel	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

Applicable External Holders **ISO D15.33**

W

Solid CBN Ceramic

Shape	Cat. No.	r_E
FX 15°	VPGT 110301R-FX	0.1
	110301L-FX	0.1
	110302R-FX	0.2
	110302L-FX	0.2
FX Finishing 15°	VPET 1103003R-FX	0.03
	1103003L-FX	0.03
	110301R-FX	0.1
	110301L-FX	0.1
	110302R-FX	0.2
	110302L-FX	0.2
FY 15°	VPGT 110301R-FY	0.1
	110301L-FY	0.1
	110302R-FY	0.2
	110302L-FY	0.2
FY Finishing 15°	VPET 1103003R-FY	0.03
	1103003L-FY	0.03
	110301R-FY	0.1
	110301L-FY	0.1
	110302R-FY	0.2
	110302L-FY	0.2