Polishing Stones



| 砥粒 (Grain) | 硬度 (Hardness) | 結合剤 (Bond) | 本数 (Pack) |
|---------------|---------------------|---------------|-----------------------------|
| WA | 中軟 (Medium Soft) | ٧ | 20 [*] (20pcs.) |

■粒度(Grit)

#150 #400 #220 #600 #320

■用涂:

アルミニウム金型及びアルミ

■性能:

特殊な樹脂を含侵させ処理された中硬度の砥 石です。特殊な樹脂によって素早く新しい砥粒 が保て、目詰まりを防ぎます。必ず研磨液をご使 用ください。



Delivery

出荷日

3日目発送

非在庫品

■Application:

Aluminum moulds and Alminum.

Features:

This medium hard stone is processed with infiltration of special made resin. This special resin constantly keeps new grains, peventing from clogging up. Please be sure, use this stone with polishing liquid.

| ■サイズ(Size | e:mm) | |
|-----------|---|-------|
| 3× 6×150 | | |
| 3×13×150 | *************************************** | |
| 6× 6×150 | | |
| 6×13×150 | | 特殊サイズ |

ブラックストーン BLACK STONE AM BLACK STONE 2000

| 砥 粒 | 硬度 | 結合剤 | 本数 |
|---------|---------------------|--------|------------------------------|
| (Grain) | (Hardness) | (Bond) | (Pack) |
| С | 中軟 (Medium Soft) | ٧ | 20 [*] (20 pcs.) |

■主な粒度(Grit)

| #120 | #400 | #1200 |
|------|-------|-------|
| #180 | #600 | #1500 |
| #240 | #800 | #2000 |
| #320 | #1000 | #3000 |

■用途:

一般金型·硬質材料金型等

■性能:

シャープな刃先を持ち金型の細部形状に迅速 に、馴染むように設計された、中軟度のSic砥粒 の砥石。ダイヤモンドペースト使用の前工程に 有効で、鏡面仕上げ等の面租度を要求される 金型に最適。硬質材料の金型研磨にも適応。

■Application:

General mold for hard material mold

Features:

This stone is made of medium soft SIC grains with sharp points designed to swiftly fit to detail forms of mold. It is best suitable to operations before diamond paste processing and best for mold which needs fine finishing, such as mirror finishing. Also suitable for polishing hard material mold.

■サイズ(Size:mm)

| _ > > \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ | | |
|---|----------|----------|
| 1× 6×100 | 2×13×100 | 5×13×150 |
| 2× 6×100 | 3×13×100 | |
| 3× 6×100 | 3× 6×150 | |
| 1×13×100 | 3×13×150 | 特殊サイズ |



