

◆ K固定 / KK固定 / KB固定 ストッパー付 / KBL固定 ストッパー(左)付

車輪種類	金具種類	車輪径 mm	最大許容荷重 kg(N)	リム幅 mm	車輪取付幅 mm	取付高 mm	取付座 mm	取付ピッチ mm	取付穴 mm	軸径 mm	自重												
											K kg	KK kg	KB kg	KBL kg									
W	K KB	75	80(780)	32	36	103	91 × 68	63 × 40	9.5	10	0.43	—	0.49	—									
WW*			60(580)								0.42	—	0.48	—									
LW*			60(580)								0.42	—	0.48	—									
UW			120(1170)								0.48	—	0.54	—									
WUW			80(780)								0.49	—	0.55	—									
MC			120(1170)								0.42	—	—	—									
W	K KK KB KBL	100	130(1270)	35	43	144	115×79 KK 100×96	80×45 KK 60×60 -71×71	11	12	0.84	0.73	0.96	0.95									
SST			130(1270)								0.82	0.71	0.94	0.93									
WW			80(780)								0.81	0.70	0.93	0.92									
LW			80(780)								0.81	0.70	0.93	0.92									
TW			100(980)								0.84	0.73	0.96	0.95									
UW			180(1760)								0.89	0.78	1.01	1.00									
WUW			130(1270)								0.89	0.78	1.01	1.00									
MC			K/KB								180(1760)	0.84	0.73	—	—								
W			K KK KB KBL								130	180(1760)	42	53	177	137×93 KK 120× 125	100×56 KK 75×75 -90×90	11.5	20	1.62	1.52	1.79	1.79
SST												180(1760)								1.59	1.49	1.76	1.76
WW	140(1370)	1.56		1.46	1.73	1.73																	
LW	140(1370)	1.56		1.46	1.73	1.73																	
UW	250(2450)	1.70		1.60	1.87	1.87																	
WUW	180(1760)	1.73		1.63	1.90	1.90																	
MC	K/KB	250(2450)		1.60	1.50	—	—																
W	K KK KB KBL	150		200(1960)	45	56	198	137×93 KK 120× 125	100×56 KK 75×75 -90×90	11.5		20								1.86	1.74	1.98	1.98
SST			200(1960)	1.90							1.78		2.02	2.02									
WW			160(1560)	1.84							1.72		2.00	2.05									
LW			160(1560)	1.84							1.72		1.99	1.99									
UW			300(2940)	2.02							1.90		2.16	2.15									
WUW			200(1960)	2.02							1.90		2.15	2.15									
MC			K/KB	300(2940)							1.97		1.85	—	—								
W*			K KB KBL	180							230(2250)		45	56	240	151 × 100	112 × 63	11.5	20	2.85	—	3.06	3.04
W	K KB KBL	200	250(2450)	45	56	250	151 × 100	112 × 63	11.5	20	3.08	—	3.29	3.27									
SST			250(2450)								3.06	—	3.27	3.25									
WW			200(1960)								3.03	—	3.24	3.22									
LW			200(1960)								3.03	—	3.24	3.22									
UW			400(3920)								3.62	—	3.83	3.81									
WUW			250(2450)								3.67	—	3.88	3.86									
MC			K								400(3920)	3.51	—	—	—								
W	K	250	330(3230)	50	90	305	200 × 140	140 × 80	14	25	5.78	—	—	—									
LW			260(2540)								5.60	—	—	—									
UW			500(4900)	45							5.93	—	—	—									
WUW			330(3230)	50							6.00	—	—	—									
MC			500(4900)	50							6.38	—	—	—									
W	K	300	350(3430)	50	109	374	220 × 150	160 × 90	14	25	8.15	—	—	—									
UW			550(5390)								8.27	—	—	—									
MC*			550(5390)								8.59	—	—	—									

・金具カラー仕上げ:U(三価クロメート)  
\* 受注生産:WWK-75, WWKB-75, LWK-75, LWKB-75 / WKB-180, WKBL-180 / MCK-300

適合車輪

<p><b>W CB ゴム</b> ・高弾性 ▶P.104</p> 	<p><b>SST CB スーパーソリッドゴム</b> Wゴムと比較して ・高弾性1.8倍 ・低始動抵抗2.5倍 ▶P.102</p> 	<p><b>WW CB ホワイトジェンゴム</b> ・高弾性 ・耐寒性 ・ノンマーキング ▶P.104</p> 	<p><b>LW CB ジェンゴム</b> ・高弾性 ・耐寒性 ▶P.97</p> 
<p><b>TW CB ゴム</b> ・高弾性 ▶P.103 韓国製</p> 	<p><b>UW CB ウレタン</b> ・耐衝撃性 ・耐油性 ▶P.103</p> 	<p><b>WUW CB 抗菌ホワイトウレタン</b> ・抗菌性 ・高弾性 ・耐油性 ▶P.104</p> 	<p><b>MC JBB モノマーキャストینگナイロン</b> ・耐薬品性 ・耐油性 ・耐摩耗性 ▶P.97</p> 

▶車輪の詳細資料はP.95~P.104をご覧ください。