Cable Cutter and Uninsulated Ferrules

Cable cutter	Ferrule, uninsulated, tin plated, electrolytic copper, gastight crimped



Item No.	Pack. Unit
Cable cutter,	
cutting Cu and Al conductors up to 35 mm²	
206-118	1

Item No.	Pack. Unit
Ferrule, uninsulated	
216-413	50
216-414	50
216-424	50
216-425	50
216-435	50

Ferrules

Technical Data

Ferrule, uninsulated,

sleeve for 25 mm²/AWG 4,
25 mm strip length,
L: 25 mm,
D: 9.5 mm, D2: 7.3 mm
216-413

Ferrule, uninsulated,

sleeve for 35 mm²/AWG 2,
25 mm strip length,
L: 25 mm,
D: 11 mm, D2: 8.3 mm
216-414

Ferrule, uninsulated,

sleeve for 35 mm²/AWG 2,
30 mm strip length,
L: 30 mm,
D: 11 mm, D2: 8.3 mm
216-424

Ferrule, uninsulated,

sleeve for 50 mm²/AWG 1,
30 mm strip length,
L: 30 mm,
D: 13 mm, D2: 10.3 mm
216-425

Ferrule, uninsulated,

sleeve for 50 mm²/AWG 1,
35 mm strip length,
L: 35 mm,
D: 13 mm, D2: 10.3 mm
216-435

Cutting a conductor.

A perfect gastight crimp, both electrically and mechanically reliable.