

# Shaft Supports Bottom Mount Split (Machined)

## Standard / Wide

■ **Features:** Screw mount from underside is effective when the mounting host is too thin to tap, and in space limited applications.

■ **Standard**

Type	M Material	S Surface Treatment	A Accessory
SHSPB	S45C	Black Oxide	Hex Socket Head Cap Screw 2 pcs.
SHSPM	Equivalent	Electroless Nickel Plating	Hex Socket Head Cap Screw 2 pcs. (SUS)
SHSPS	SUS304	-	
SHSPA	Aluminum Alloy	Clear Anodize	
SHSPK		Black Anodize	Hex Socket Head Cap Screw 2 pcs.

This Split Type enables shafts to be mounted from above.

☞ P.250

Part Number Type	D	H Selection				L	H <sub>1</sub>	T	L <sub>1</sub>	Tightening Screw M	M <sub>1</sub>	d	d <sub>1</sub>	l	C	Unit Price													
		SHSPB	SHSPM	SHSPS	SHSPA											SHSPK													
SHSPB SHSPM SHSPS SHSPA SHSPK	8	25	30		26	H+10	12	16	M4 Depth 8	4	4.5	8	4.5	2															
	10	25	30		32										20														
	12	25	30		34										21														
	13	25	30		44										23														
	15	25	30	40	44	H+17	16 (15)	28	M6 Depth 12	6	6.6	11	6.5	2															
	16	25	30	40	50										34														
	18		30	40	50	50	H+20	36	M8 Depth 16	8	9	14	9	3															
	20		30	40	50	70									48														
	25		30	40	50	76	H+30	22 (20)	56	M8 Depth 16	8	9	14	9	3														
	30		40	50	60																								
	35		40	50	60																								
	40		40	50	60																								

⊖ Values in ( ) are the T dimensions of SHSPA and SHSPK (Aluminum).

■ **Wide**

Type	M Material	S Surface Treatment	A Accessory
SHSPBN	S45C	Black Oxide	Hex Socket Head Cap Screw 2 pcs.
SHSPMN	Equivalent	Electroless Nickel Plating	Hex Socket Head Cap Screw 2 pcs. (SUS)
SHSPSN	SUS304	-	

Part Number Type	D	H Selection				L	H <sub>1</sub>	T	T <sub>1</sub>	L <sub>1</sub>	Tightening Screw M	M <sub>1</sub>	d	d <sub>1</sub>	l	C	Unit Price												
		SHSPBN	SHSPMN	SHSPSN																									
SHSPBN SHSPMN SHSPSN	10	25	30		37	H+11	24	16	22	M6 Depth 12	M4	6.6	11	6.5	2														
	12	25	30		39	H+12	24	16	24																				
	15	25	30	40	46	H+14	26	18	28	M8 Depth 16	M6	9	14	9	2														
	16	25	30	40	48																								
	20		30	40	50	H+18	30	20	34	M8 Depth 16	M6	9	14	9	3														
	25		30	40	50											52													
	30		40	50	60	H+30	35	25	44	M8 Depth 16	M6	9	14	9	3														
	35		40	50	60											48													
	40		40	50	60											66													
	40		40	50	60											72	40	24	54										

Ordering Example: Part Number - H  
SHSPB10 - 25  
SHSPB16 - 30

Alterations: Part Number - HC  
SHSPB25 - HC31.5  
SHSPS16 - HC35.6  
⊖ Alterations are not available for Wide Type. ⊕ Express Service is not available.

Alteration	Code	Spec.
Mounting Height 	HC	Changes shaft mounting height. Change H to HC to specify height. ⊖ Specify HC in 0.1mm increments. ⊕ Specifiable Range Hmin.<HC<Hmax. Ordering Code HC35.6