

Mega-Pixel CCTV Lenses / Height Adjustment Screw Set for Post Clamps / Rear Converter / Setscrews







Material: Aluminum (Body) S Surface Treatment: Black Anodize (Body)

Mega-Pixel CCTV Lenses	Mega-	Pixel	CCTV	Lenses
------------------------	-------	-------	-------------	--------

CCTV Lenses


Part Number	Part Number		Part Number		Aperture	Max. applicable	WD (Shooting	TV Distantian	Filter Screw	-	_	(a)	(la)	Weight	Unit Price	Volume Discount Rate
Type	No.	Distance	tance (FNO)		Distance) (mm)	Filter Screw Dia. (MxPitch)		U	(a)	(b)	g	1 ~ 4 pc(s).	5 ~ 20 pcs.			
	6	6	1.4~close	1/2 inch	200~∞	-0.96%	30.5x0.5	37.5	32	5.8	5.6	65				
	8	8	1.4~close	2/3 inch	100~∞	-0.10%	30.5x0.5	28.2	33.5	4.7	4.5	63				
	12	12	1.4~close	2/3 inch	150~∞	-0.10%	30.5x0.5	28.2	33.5	4.7	4.5	62				
MLCV	16	16	1.4~close	2/3 inch	300~∞	-0.10%	30.5x0.5	28.2	33.5	5.8	5.6	60				
	25	25	1.4~close	2/3 inch	250~∞	-0.30%	25.5x0.5	31.5	29	5.8	5.6	45				
	35	35	2.0~close	2/3 inch	250~∞	-0.02%	25.5x0.5	38.5	29	5.8	5.6	55				
	50	50	2.8~close	2/3 inch	500~∞	-0.20%	25.5x0.5	38.5	29	5.8	5.6	55				

For orders larger than indicated quantity, please check with WOS.

		-													
Par	Part Number		Focal	Aperture	Max. applicable	WD (Shooting	TV Distortion	Filter Screw			(a)	(b)	Weight	Unit Price	Volume Discount Rate
Ty	/pe	No.	Distance	(FNO)	CCD	WD (Shooting Distance) (mm) TV Distortion Filt Dia.		Dia. (MxPitch)	_		(a)	(D)	g	1 ~ 4 pc(s).	5 ~ 20 pcs.
		6	6	1.4~close	1/2 inch	200~∞	-1.60%	27x0.5	30.0	30	5	5.3	60		
		8	8	1.3~close	2/3 inch	200~∞	-1.90%	25.5x0.5	34.5	29	5	5.3	60		
	ĺ	12	12	1.4~close	1/2 inch	300~∞	-0.30%	27x0.5	34.5	30	5	5.3	60		
LC	CV	16	16	1.4~close	2/3 inch	400~∞	-0.60%	27x0.5	24.5	30	5	5.3	40		
		25	25	1.4~close	2/3 inch	500~∞	-0.60%	27x0.5	24.5	30	5	5.3	45		
	35	35	1.9~close	2/3 inch	500~∞	0.08%	27x0.5	29.0	30	5	5.3	50			
		50	50	1.8~close	2/3 inch	1000~∞	0.20%	30.5x0.5	37.0	32	5	5.3	60		

(a)(b) dimensions are the reference height for when the knob is fixed. ()Can be used for CCDs other than the most optimal CCD, but four corners of images may be slightly clipped (Vignetting). (*)For orders larger than indicated quantity, please check with WOS.






Part Number	Unit Price	Volume Discount Rate			
r art Number	1 ~ 4 pc(s).	5 ~ 20 pcs.			
LRC					

- For orders larger than indicated quantity, please check with WOS.
- Magnification can be increased without changing the shooting distance by attaching this lens between the lens and CCD camera (Magnification x2).
 The field of view becomes narrower (See P.2028 Table 1.)
 Use by putting it between the CCD camera and C mounting sides of all the
- lenses / auto macro rings.

Features: Fits the inch tapped thread on CCD cameras. Can be used to mount the camera on solid objects





Part Num	ber	Unit Price	Volume Dis	iscount Rate							
Туре	L	1 ~ 3 pack(s).	4 ~ 8 packs.	9 ~ 30 packs.							
LCK	8										
LUK	12										
Cold by the section (A section section Figure)											

- Sold by the package (A package contains 5 pieces)
 For orders larger than indicated quantity, please check with WOS.

Caution: The size of hex socket is equivalent to M6. When tightening, use hex wrench for M6.

Features: Mounts below Post Clamps to provide easy manual height adjustments (Max. recommended stroke 5mm). Best suited for camera and sensor position adjustments. Details: P.2170



Type W/ Double Nuts W/O Double Nut	s Main Body Nut	SSurface Treatment	Accessory	*2 For Double Nut type
CLAWM CLAJM CLAWB CLAJB	S45C SUM23 Equivalent Equivalent		Hex Socket Head Cap Screw (Stainless Steel) Hex Socket Head Cap Screw	$\frac{B^{-1}C}{(1)}$
CB screws for Black products.	k Oxide produ	cts, SCB for El		XXX

Part Number													М	lar almala al		Unit	Price				
Type W/ Double Nuts W/O Double Nuts		р.		_		A	В	С	Н	P	D ₂	Dз	M	d1	d2	Move Distance	Included Screws	W/ Doul	ole Nuts	W/O Dou	ible Nuts
			D ₁ ^											Distance	OCIEWS	CLAWM	CLAWB	CLAJM	CLAJB		
		10		30		11	14	9.5	16	28	4				M4 - 8, 1pc.						
	CLAJM	12	+0.05 +0.01 33 40		6	12	16	10	18	30	5 4.	4.6 3.4	3.4		M4 - 10, 1pc.						
CLAWM		15			1 '	13	20	12	22	35				_	M5 - 12, 1pc.						
CLAWB	CLAJB	20		38	8 17	15	25	15	28	40	C F:	E 7	5.7 4.6	1 0 1	M6 - 15, 1pc.						
02		25		40		17	30	17	34	45	0	3.7			M6 - 18, 1pc.						
		30		46		19	36	21	40	55	8	6.8	5.7		M8 - 20, 1pc.						

- *1 Shows the nut portion protruding 1 mm from the main body:
 *2 When "W/O Double Nuts" is selected, double nut is not included.
 *Dit tolerance is for before the slit machining. Set screw is not included. Recommended tolerances of fitting shafts for Di: g6, f8.

