

Tubes

Fluoro Rubber Tubes Transparent Type

PUTFB
PUTFBL



Material: Fluoro Rubber

Part Number		Standard Length (m)		Configurable Length (0.5m Increment)	I.D. (mm)	O.D. Accuracy (mm)	Max. Operating Pressure (MPa)	Burst Pressure (MPa)	Mass (kg/m)	Standard		Configurable Length		
Type	O.D. (mm)	PUTFB	PUTFBL							Unit Price	Volume Discount Rate	Unit Price/m	Volume Discount Rate/m	
										1 ~ 4 pc(s).	5 ~ 10	1 ~ 4 pc(s).	5 ~ 10	
PUTFB (Standard Length)	4	10	0.5-9.5 10.5-19.5	2	±0.15	0.248	0.993	0.018						
		20												
	6	10				4	0.149	0.594	0.030					
		20												
	PUTFBL (Configurable Length)	8		10		6	0.09	0.360	0.042					
				20										
		10		10			8	0.049	0.195	0.053				
				20										

Features: Excellent in transparency and chemical resistance.

Fluoro Rubber Tubes Heat Resistant Type

PUTFG
PUTFGL



Material: Fluoro Rubber

Part Number		Standard Length (m)		Configurable Length (0.5m Increment)	I.D. (mm)	Min. Bending Radius (mm)	O.D. Accuracy (mm)	Max. Operating Pressure (MPa)	Burst Pressure (MPa)	Mass (kg/m)	Standard		Configurable Length			
Type	O.D. (mm)	PUTFG	PUTFGL								Unit Price	Volume Discount Rate	Unit Price/m	Volume Discount Rate/m		
												1 ~ 4 pc(s).	5 ~ 10	1 ~ 4 pc(s).	5 ~ 10	
PUTFG (Standard Length)	4	10	0.5-9.5 10.5-19.5	2	±0.15	-	-	0.019								
		20														
	6	10				4	20	-	-	0.031						
		20														
	PUTFGL (Configurable Length)	8		10		6	0.088	0.35	0.044							
				20												
		10		10			8	35	±0.2	-	-	0.080				
				20												

Features: Excellent in heat resistance (~ 200°C), oil resistance, ozone resistance, and chemical resistance.

Silicon Tubes

PUTC
PUTCL



Material: Silicon Rubber

RoHS10

Part Number		Standard Length (m)		Configurable Length (0.5m Increment)	I.D. (mm)	Min. Bending Radius (mm)	Mass (kg/m)	Standard		Configurable Length				
Type	O.D. (mm)	PUTC	PUTCL					Unit Price	Volume Discount Rate	Unit Price/m	Volume Discount Rate/m			
								1 ~ 4 pc(s).	5 ~ 10	1 ~ 4 pc(s).	5 ~ 10			
PUTC (Standard Length)	4	10	0.5-9.5 10.5-19.5	2	10	0.011								
		20												
	6	10					4	20	0.018					
		20												
	PUTCL (Configurable Length)	8		10			6	45	0.025					
				20										
		10		10				8	70	0.033				
				20										
	12	10		9			65	0.058						
		20												



Ordering Example
Part Number - Length
PUTFB4 - 10
PUTCL4 - 3.5

Use Inserts for Soft Tubes when connecting Silicone Tubes to One-Touch Couplings. (P.12-1390)